

# ORIGINALS

Savannah

Originals Savannah Smoked Natural Oil

2012673

190 x 19 cm  
14/3 mm

25 years  
Solidfloor™  
guarantee



## Packaging

|                          |                          |
|--------------------------|--------------------------|
| Boards per pack:         | 8 boards                 |
| m <sup>2</sup> per pack: | 2,89 m <sup>2</sup>      |
| Weight per pack:         | 21 kg                    |
| Broken lengths per pack: | 25% minimal 60 cm length |

## Dimensions

|                    |            |
|--------------------|------------|
| Length:            | 190 cm     |
| Width:             | 19 cm      |
| Thickness (total): | 14 mm      |
| Top layer:         | 2,5-3,0 mm |

## Dimensional tolerances according to EN13489

|                                       |                        |
|---------------------------------------|------------------------|
| Length:                               | 0,20%                  |
| Width:                                | 0,2 mm                 |
| Thickness:                            | Total: 14 mm ± 0,2 mm  |
| Top layer:                            | 2,5-3,0 mm             |
| Height difference between the panels: | ≤0,2 mm                |
| Squareness:                           | ≤0,2% across the width |
| Cup:                                  | ≤0,2% across the width |
| Spring:                               | ≤0,1% over the length  |
| Bend:                                 | ≤1% over the length    |

## Other Specifications

|                        |                          |
|------------------------|--------------------------|
| Formaldehyde emission: | E1                       |
| Insulation value:      | R=0,11m <sup>2</sup> k/w |
| Brinell hardness:      | Average HB 3.7           |

## Additional specifications

|                   |                   |
|-------------------|-------------------|
| Bevel:            | 1 mm              |
| Construction:     | 3-layerd          |
| Moisture content: | 7% +/- 2%         |
| Locking system:   | Tongue and groove |

## Instructions and Maintenance

Oil immediately after installation.  
Maintain with Solidfloor™ Ultimate Hardwax Natural & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit [www.solidfloor.com](http://www.solidfloor.com) for more information).